
sphinxcontrib-vcs Documentation

Release 0.1

Tetsuya Morimoto

Apr 18, 2020

CONTENTS

1	Git directive	3
1.1	Options	3
1.2	Top commit history	3
1.3	Particular commit log	25
2	Acknowledgments	27
3	Indices and tables	29

Contents:

CHAPTER ONE

GIT DIRECTIVE

contents

- *Options*
- *Top commit history*
- *Particular commit log*

1.1 Options

The repository directive takes these options.

- **number_of_revisions:** positive integer
Set the number of revision to show commit history. Default is 10.
- **revision:** revision string
Set revision string to show particular commit history.
- **with_ref_url:**
Set as a flag to show commit URL on repository hosting service. It supports [github](#) and [bitbucket](#).
- **include_diff:**
Set as a flag to show diff text with commit history. The diff text is hidden with initial state. Clicking around commit message shows the diff text.

1.2 Top commit history

```
.. git:::  
  :number_of_revisions: 20  
  :with_ref_url:  
  :include_diff:
```

- **update README by Tetsuya Morimoto at 2019-11-06 02:03:05**
0806b703030e8634d97d71c58ed56631f77a8a64

```
diff --git a/README.md b/README.md
index 73e9585..fd8aad4 100644
--- a/README.md
+++ b/README.md
@@ -32,6 +32,10 @@ For more information have a look at [the documentation] (https://
↪/sphinxcontrib-vc

## ChangeLog

+### 0.2.2 (2019-11-06)
+
+* fix packaging issue: cannot import sphinxcontrib.repository
+
### 0.2.1 (2019-08-04)

* fix wrong Docutils DTD list_item node thanks to amedama41
```

- **fix to be able to import sphinxcontrib.repository** by Tetsuya Morimoto at 2019-11-06 01:56:21
2b2ae4e5f404b3aef281d231203e724abc9a6fa5

```
diff --git a/setup.py b/setup.py
index 9e90796..1ec0c6c 100644
--- a/setup.py
+++ b/setup.py
@@ -1,6 +1,6 @@
import re
from os import path
-from setuptools import setup
+from setuptools import find_packages, setup

version_py = open('sphinxcontrib/vcs.py').read()
metadata = dict(re.findall('__([a-z]+)__ = ' '([^\']+)''', version_py))
@@ -39,7 +39,7 @@ setup(
    author_email='tetsuya.morimoto@gmail.com',
    zip_safe=False,
    platforms='any',
-   packages=['sphinxcontrib'],
+   packages=find_packages(),
    namespace_packages=['sphinxcontrib'],
    include_package_data=True,
    install_requires=[

diff --git a/sphinxcontrib/vcs.py b/sphinxcontrib/vcs.py
index d3e7721..98f6517 100644
--- a/sphinxcontrib/vcs.py
+++ b/sphinxcontrib/vcs.py
@@ -9,7 +9,7 @@ from sphinx.util.osutil import copyfile

from .repository import GitRepository

__version__ = '0.2.1'
__version__ = '0.2.2'

logger = logging.getLogger(__name__)
```

- Bump urllib3 from 1.24.1 to 1.24.2 by Tetsuya Morimoto at 2019-11-06 01:31:35
8729d58324940263f5774ddf6150cdb649f5768d

- Bumps [urllib3](https://github.com/urllib3/urllib3) from 1.24.1 to 1.24.2. - [Release notes](https://github.com/urllib3/urllib3/releases) - [Changelog](https://github.com/urllib3/urllib3/blob/master/CHANGES.rst) - [Commits](https://github.com/urllib3/urllib3/compare/1.24.1...1.24.2)

Signed-off-by: dependabot[bot] <support@github.com> by *dependabot[bot]* at 2019-10-21 17:38:12
[5580413dacfa8820d15076f06abf96a112868191](#)

```
diff --git a/requirements.txt b/requirements.txt
index 8c7d5a7..b7cef77 100644
--- a/requirements.txt
+++ b/requirements.txt
@@ -25,4 +25,4 @@ sphinxcontrib-jsmath==1.0.1
 sphinxcontrib-qthelp==1.0.2
 sphinxcontrib-serializinghtml==1.1.3
 sphinxcontrib-vcs==0.2.0
-urllib3==1.24.1
+urllib3==1.24.2
```

- **update version 0.2.1 by Tetsuya Morimoto at 2019-08-04 05:52:37**
[694004f22607a734ca15f83ff30cbfb6891283d7](#)

```
diff --git a/README.md b/README.md
index 078fada..73e9585 100644
--- a/README.md
+++ b/README.md
@@ -32,6 +32,10 @@ For more information have a look at [the documentation] (https://
 ↵/sphinxcontrib-vc

 ## ChangeLog

+### 0.2.1 (2019-08-04)
+
++ fix wrong Docutils DTD list_item node thanks to amedama41
+
### 0.2.0 (2018-11-17)

 * drop Python 2.7 support and mercurial feature
diff --git a/sphinxcontrib/vcs.py b/sphinxcontrib/vcs.py
index 86d1d67..d3e7721 100644
--- a/sphinxcontrib/vcs.py
+++ b/sphinxcontrib/vcs.py
@@ -9,7 +9,7 @@ from sphinx.util.osutil import copyfile

 from .repository import GitRepository

-_version_ = '0.2.0'
+_version_ = '0.2.1'

 logger = logging.getLogger(__name__)
```

- fix to generate well-formed docutils document tree by *Tetsuya Morimoto* at 2019-08-04 05:40:46
[33be27e6f95f8470876a66e2365a58e14436ed38](#)

- fix to generate well-formed docutils document tree by amedama41 at 2019-08-02 13:27:55
f15e4911aae736a06ed97ad3c3140eb97e6e75e

```
diff --git a/sphinxcontrib/vcs.py b/sphinxcontrib/vcs.py
index e809400..86d1d67 100644
--- a/sphinxcontrib/vcs.py
+++ b/sphinxcontrib/vcs.py
@@ -76,14 +76,17 @@ class GitDirective(BaseDirective):

    def get_changelog(self, repo, commit):
        item = nodes.list_item()
+
        para = nodes.paragraph()

-
        item.append(self._make_message_node(commit.message, commit.hexsha))
-
        item.append(nodes.inline(text=' by '))
-
        item.append(nodes.emphasis(text=commit.author.name))
-
        item.append(nodes.inline(text=' at '))
+
        para.append(self._make_message_node(commit.message, commit.hexsha))
+
        para.append(nodes.inline(text=' by '))
+
        para.append(nodes.emphasis(text=commit.author.name))
+
        para.append(nodes.inline(text=' at '))

        commit_date = datetime.fromtimestamp(commit.authored_date)
-
        item.append(nodes.emphasis(text=commit_date))
+
        para.append(nodes.emphasis(text=commit_date))

+
        item.append(para)

    if OPTION_WITH_REF_URL in self.options:
        ref_url = repo.get_commit_url(commit.hexsha)
```

- update tox test environment and drop 3.4 support by Tetsuya Morimoto at 2019-04-13 03:04:30
d2b208a5576d1012ff0de9ae1b3bb674ea62181f

```
diff --git a/.travis.yml b/.travis.yml
index e39d492..743b766 100644
--- a/.travis.yml
+++ b/.travis.yml
@@ -1,10 +1,6 @@
 language: python
 matrix:
   include:
-
-   - os: linux
-     sudo: required
-     python: 3.4
-     env: TOXENV=py34
-   - os: linux
-     sudo: required
-     python: 3.5
@@ -13,6 +9,10 @@ matrix:
   sudo: required
   python: 3.6
   env: TOXENV=py36
+
+   - os: linux
+     sudo: required
+     python: 3.7
+     env: TOXENV=py37
```

(continues on next page)

(continued from previous page)

```

install: pip install docutils tox
script: tox
diff --git a/setup.py b/setup.py
index d3527cc..9e90796 100644
--- a/setup.py
+++ b/setup.py
@@ -22,7 +22,6 @@ setup(
    'Intended Audience :: Developers',
    'Operating System :: OS Independent',
    'Programming Language :: Python :: 3',
-   'Programming Language :: Python :: 3.4',
    'Programming Language :: Python :: 3.5',
    'Programming Language :: Python :: 3.6',
    'Programming Language :: Python :: 3.7',
diff --git a/tox.ini b/tox.ini
index 7ed87a0..51a8ca1 100644
--- a/tox.ini
+++ b/tox.ini
@@ -1,16 +1,18 @@
[tox]
-envlist = py34, py35, py36, py37
+envlist = py35, py36, py37

[testenv]
passenv =
    LANG
    LC_ALL
+; TODO: Sphinx 2.0.x raise No module named 'sphinxcontrib.serializinghtml'
deps=
    nose
    mock
    flake8
    reportlab
    sphinx-testing
+   Sphinx==1.8.5
commands=
    nosetests -v
    flake8 setup.py sphinxcontrib/ tests/

```

- **update requirements.txt** by *Tetsuya Morimoto* at *2019-04-13 02:51:19*
f9d252516ddee7f9251f0cdf94cdf8b68b9ee02f

```

diff --git a/requirements.txt b/requirements.txt
index adb4ale..8c7d5a7 100644
--- a/requirements.txt
+++ b/requirements.txt
@@ -1,23 +1,28 @@
alabaster==0.7.12
Babel==2.6.0
-certifi==2018.10.15
+certifi==2019.3.9
chardet==3.0.4
docutils==0.14
gitdb2==2.0.5
GitPython==2.1.11
-idna==2.7

```

(continues on next page)

(continued from previous page)

```
+idna==2.8
 imagesize==1.1.0
-Jinja2==2.10
-MarkupSafe==1.1.0
-packaging==18.0
-Pygments==2.2.0
-pyparsing==2.3.0
-pytz==2018.7
-requests==2.20.1
-six==1.11.0
+Jinja2==2.10.1
+MarkupSafe==1.1.1
+packaging==19.0
+Pygments==2.3.1
+pyparsing==2.4.0
+pytz==2019.1
+requests==2.21.0
+six==1.12.0
 smmap2==2.0.5
 snowballstemmer==1.2.1
-Sphinx==1.8.2
+Sphinx==2.0.1
+sphinxcontrib-applehelp==1.0.1
+sphinxcontrib-devhelp==1.0.1
+sphinxcontrib-htmlhelp==1.0.2
+sphinxcontrib-jsmath==1.0.1
+sphinxcontrib-qthelp==1.0.2
+sphinxcontrib-serializinghtml==1.1.3
 sphinxcontrib-vcs==0.2.0
-sphinxcontrib-websupport==1.1.0
 urllib3==1.24.1
```

- **migrate document hosting site to readthedocs.org** by Tetsuya Morimoto at 2018-11-17 13:32:27
776146fc9e456a0733eaa97d0f7679c8eb5d7c5e

```
diff --git a/README.md b/README.md
index 4642e3c..078fada 100644
--- a/README.md
+++ b/README.md
@@ -24,7 +24,7 @@ Then, repository directives are available as follows.
 :with_ref_url:
 :include_diff:

-For more information have a look at [the documentation] (https://pythonhosted.org/
-`-sphinxcontrib-vcs`).
+For more information have a look at [the documentation] (https://sphinxcontrib-
-`-vcs.readthedocs.io`).

## Acknowledgments
```

- **add requirements.txt to build documentation on readthedocs.org** by Tetsuya Morimoto at 2018-11-17 13:26:21 40b6d3e2bd27d675566027131ade069f6989a7e6

```
diff --git a/.travis.yml b/.travis.yml
index b6798eb..e39d492 100644
```

(continues on next page)

(continued from previous page)

```

--- a/.travis.yml
+++ b/.travis.yml
@@ -13,10 +13,6 @@ matrix:
    sudo: required
    python: 3.6
    env: TOXENV=py36
-   - os: linux
-     sudo: required
-     python: 3.7
-     env: TOXENV=py37

    install: pip install docutils tox
    script: tox
diff --git a/requirements.txt b/requirements.txt
new file mode 100644
index 000000..adb4ale
--- /dev/null
+++ b/requirements.txt
@@ -0,0 +1,23 @@
+alabaster==0.7.12
+Babel==2.6.0
+certifi==2018.10.15
+chardet==3.0.4
+docutils==0.14
+gitdb2==2.0.5
+GitPython==2.1.11
+idna==2.7
+imagesize==1.1.0
+Jinja2==2.10
+MarkupSafe==1.1.0
+packaging==18.0
+Pygments==2.2.0
+pyparsing==2.3.0
+pytz==2018.7
+requests==2.20.1
+six==1.11.0
+smmap2==2.0.5
+snowballstemmer==1.2.1
+Sphinx==1.8.2
+sphinxcontrib-vcs==0.2.0
+sphinxcontrib-websupport==1.1.0
+urllib3==1.24.1

```

- **update travis configuration** by Tetsuya Morimoto at 2018-11-17 13:14:21
7f2a18b7b48e075c7ce5d49ca7d0edeb71fd0dd6

```

diff --git a/.travis.yml b/.travis.yml
index d8ca2cd..b6798eb 100644
--- a/.travis.yml
+++ b/.travis.yml
@@ -1,11 +1,22 @@
 language: python
-python: 3.6
-env:
- matrix:
-   - TOXENV=py34

```

(continues on next page)

(continued from previous page)

```
-      - TOXENV=py35
-      - TOXENV=py36
-      - TOXENV=py37
+matrix:
+  include:
+    - os: linux
+      sudo: required
+      python: 3.4
+      env: TOXENV=py34
+    - os: linux
+      sudo: required
+      python: 3.5
+      env: TOXENV=py35
+    - os: linux
+      sudo: required
+      python: 3.6
+      env: TOXENV=py36
+    - os: linux
+      sudo: required
+      python: 3.7
+      env: TOXENV=py37

install: pip install docutils tox
script: tox
```

- **update travis configuration** by Tetsuya Morimoto at 2018-11-17 13:07:22
364870b26c8424fbfbfad426916d3c4e9cca9840

```
diff --git a/.travis.yml b/.travis.yml
index bc36e79..d8ca2cd 100644
--- a/.travis.yml
+++ b/.travis.yml
@@ -1,10 +1,11 @@
 language: python
-python: 2.7
+python: 3.6
 env:
   matrix:
-      - TOXENV=py27
-      - TOXENV=py33
-      - TOXENV=py34
+      - TOXENV=py35
+      - TOXENV=py36
+      - TOXENV=py37

install: pip install docutils tox
script: tox
```

- **update version 0.2.0** by Tetsuya Morimoto at 2018-11-17 13:00:55
75e4930ce5932c17ae890151ebd5c3e18fde8c93

```
diff --git a/CHANGELOG.md b/CHANGELOG.md
deleted file mode 100644
index 6c3c0c1..0000000
--- a/CHANGELOG.md
+++ /dev/null
```

(continues on next page)

(continued from previous page)

```

@@ -1,6 +0,0 @@
-
-## ChangeLog
-
-### 0.1.0 (2016-09-06)
-
-* first release
diff --git a/README.md b/README.md
index 2738134..4642e3c 100644
--- a/README.md
+++ b/README.md
@@ -30,3 +30,13 @@ For more information have a look at [the documentation] (https://
 ↵/pythonhosted.org

*sphinxcontrib-vcs* is inspired from the [sphinx-git] (https://github.com/
 ↵OddBloke/sphinx-git) .

+## ChangeLog
+
+### 0.2.0 (2018-11-17)
+
+* drop Python 2.7 support and mercurial feature
+* support internal git repository such as GitHub Enterprise
+
+### 0.1.0 (2016-09-06)
+
+* first release
diff --git a/setup.cfg b/setup.cfg
index 31e9f22..27c1577 100644
--- a/setup.cfg
+++ b/setup.cfg
@@ -7,12 +7,5 @@ formats = gztar
 [wheel]
universal = 1

-[aliases]
-release = check -r -s register sdist bdist_wheel upload
-
-[check]
-strict = 1
-restructuredtext = 1
-
[upload_sphinx]
upload-dir = docs/_build/html
diff --git a/setup.py b/setup.py
index 298ec4a..d3527cc 100644
--- a/setup.py
+++ b/setup.py
@@ -1,31 +1,21 @@
import re
+from os import path
from setuptools import setup

-
-try:
-    import pypandoc
-    long_description = '\n'.join([

```

(continues on next page)

(continued from previous page)

```
-         pypandoc.convert('README.md', 'rst'),
-         pypandoc.convert('CHANGELOG.md', 'rst'),
-     ])
-except (IOError, ImportError):
-     long_description = ''
-
    version_py = open('sphinxcontrib/vcs.py').read()
    metadata = dict(re.findall('__([a-z]+)__ = '(['^']+)', version_py))
    desc = 'Sphinx extension to show commit history in version control system'
-
    requires = [
-        'GitPython',
-        'Sphinx',
-    ]
-
+cur_dir = path.abspath(path.dirname(__file__))
+with open(path.join(cur_dir, 'README.md')) as f:
+    long_description = f.read()
-
    setup(
        name='sphinxcontrib-vcs',
        version=metadata['version'],
        description=desc,
        long_description=long_description,
+       long_description_content_type='text/markdown',
        classifiers=[
            'License :: OSI Approved :: BSD License',
            'Development Status :: 4 - Beta',
@@ -53,7 +43,10 @@ setup(
            packages=['sphinxcontrib'],
            namespace_packages=['sphinxcontrib'],
            include_package_data=True,
-           install_requires=requires,
+           install_requires=[
+               'GitPython',
+               'Sphinx',
+           ],
            tests_require=[
                'flake8', 'mock', 'nose', 'reportlab', 'sphinx-testing',
            ],
diff --git a/sphinxcontrib/vcs.py b/sphinxcontrib/vcs.py
index dee234b..e809400 100644
--- a/sphinxcontrib/vcs.py
+++ b/sphinxcontrib/vcs.py
@@ -9,7 +9,7 @@ from sphinx.util.osutil import copyfile

from .repository import GitRepository

-__version__ = '0.1.0'
+__version__ = '0.2.0'

logger = logging.getLogger(__name__)
```

-
- support internal git repository like GitHub Enterprise by Tetsuya Morimoto at 2018-11-17 12:17:31 464ec78d4b4ea7d0373c8b9e426971a9fdb8874b

```

diff --git a/.gitignore b/.gitignore
index db4561e..9be4ee2 100644
--- a/.gitignore
+++ b/.gitignore
@@ -1,3 +1,5 @@
+build/
+
 # Byte-compiled / optimized / DLL files
 __pycache__/
 *.py[cod]
diff --git a/sphinxcontrib/repository/_git.py b/sphinxcontrib/repository/_git.py
index a4f560f..db40916 100644
--- a/sphinxcontrib/repository/_git.py
+++ b/sphinxcontrib/repository/_git.py
@@ -12,7 +12,7 @@ class GitRepository(Repo):
     EMPTY_TREE_SHA = '4b825dc642cb6eb9a060e54bf8d69288fbee4904'
     URL_PATTERN = re.compile(
         r"""
-        git@.*?: (?P<account>.*?)/(?P<repository_name>.*?)\.\git
+        git@(?P<domain>.*?): (?P<account>.*?)/(?P<repository_name>.*?)\.\git
         |https://github.com/(?P<account>.*?)/(?P<repository_name>.*?)\.\git
         """, re.VERBOSE
     )
@@ -78,12 +78,9 @@ class GitRepository(Repo):
     if len(self._commits) == 0:
         self.get_commits()

+    url = self.remotes.origin.url
    site = find_hosting_site(self.remotes.origin.url)
-    if site is None:
-        return ''
-
-    return make_commit_url(
-        self.URL_PATTERN, self.remotes.origin.url, site, revision)
+    return make_commit_url(self.URL_PATTERN, url, site, revision)

    def get_repo(path):
diff --git a/sphinxcontrib/repository/utils.py b/sphinxcontrib/repository/utils.py
index 0a4dcdf..c7de869 100644
--- a/sphinxcontrib/repository/utils.py
+++ b/sphinxcontrib/repository/utils.py
@@ -10,6 +10,10 @@ HOSTING_SERVICE = {
     'site': 'https://bitbucket.org',
     'commit_template': '{site}/{user}/{repository}/commits/{sha}',
 },
+    'internal': {
+        'site': None,
+        'commit_template': '{site}/{user}/{repository}/commit/{sha}',
+    },
}

logging.basicConfig(
@@ -24,7 +28,7 @@ def find_hosting_site(url):
    return HOSTING_SERVICE['github']
 elif url.find('bitbucket.org') > 0:
    return HOSTING_SERVICE['bitbucket']

```

(continues on next page)

(continued from previous page)

```
-    return None
+    return HOSTING_SERVICE['internal']

def make_commit_url(pattern, path, site, revision):
@@ -33,10 +37,16 @@ def make_commit_url(pattern, path, site, revision):
    return ''

    info = m.groupdict()
+
+    _site = site['site']
+    if _site is None:
+        # suppose GitHub Enterprise
+        _site = 'https://%s' % info.get('domain')
+
+    account = info.get('account') or info.get('account_')
repository = info.get('repository_name') or info.get('repository_name_')
return site['commit_template'].format(
    site=site['site'],
+
+    site=_site,
    user=account,
    repository=repository,
    sha=revision,
```

- drop mercurial feature by Tetsuya Morimoto at 2018-11-17 11:45:34
c3110fa1f0c132f0b1019fe90ca190e495541df6

```
diff --git a/docs/_options.rst b/docs/_options.rst
deleted file mode 100644
index 4889ba3..0000000
--- a/docs/_options.rst
+++ /dev/null
@@ -1,27 +0,0 @@
-Options
-----
-
-The repository directive takes these options.
-
-- **number_of_revisions**: positive integer
-
- Set the number of revision to show commit history. Default is 10.
-
-- **revision**: revision string
-
- Set revision string to show particular commit history.
-
-- **with_ref_url**:
-
- Set as a flag to show commit URL on repository hosting service.
- It supports github_ and bitbucket_.
-
-.. _github: https://github.com/
-.. _bitbucket: https://bitbucket.org/
-
-- **include_diff**:
-
```

(continues on next page)

(continued from previous page)

```

- Set as a flag to show diff text with commit history.
- The diff text is hidden with initial state.
- Clicking around commit message shows the diff text.
-

diff --git a/docs/git.rst b/docs/git.rst
index 4ece3a3..a0d2a29 100644
--- a/docs/git.rst
+++ b/docs/git.rst
@@ -4,7 +4,32 @@ Git directive
 .. contents:: contents
 :local:

-.. include:: _options.rst
+Options
+-----
+
+The repository directive takes these options.
+
+- **number_of_revisions**: positive integer
+
+ Set the number of revision to show commit history. Default is 10.
+
+- **revision**: revision string
+
+ Set revision string to show particular commit history.
+
+- **with_ref_url**:
+
+ Set as a flag to show commit URL on repository hosting service.
+ It supports github_ and bitbucket_.
+
+.. _github: https://github.com/
+.. _bitbucket: https://bitbucket.org/
+
+- **include_diff**:
+
+ Set as a flag to show diff text with commit history.
+ The diff text is hidden with initial state.
+ Clicking around commit message shows the diff text.

Top commit history
-----
diff --git a/docs/index.rst b/docs/index.rst
index cba5231..43db167 100644
--- a/docs/index.rst
+++ b/docs/index.rst
@@ -12,7 +12,6 @@ Contents:
 :maxdepth: 2

 git
-
 mercurial

Acknowledgments
diff --git a/docs/mercurial.rst b/docs/mercurial.rst
deleted file mode 100644
index 6c277d4..0000000

```

(continues on next page)

(continued from previous page)

```
--- a/docs/mercurial.rst
+++ /dev/null
@@ -1,33 +0,0 @@
-Mercurial directive
=====
-
-.. note::
-
-    supports Python 2.7 only
-
-.. contents:: contents
-:local:
-
-.. include:: _options.rst
-
-Top commit history
-----
-
-:::
-
-    .. mercurial::
-        :number_of_revisions: 20
-        :with_ref_url:
-        :include_diff:
-
-
-Particular commit log
-----
-
-:::
-
-    .. mercurial::
-        :revision: 33:g87922kd38d8
-        :with_ref_url:
-        :include_diff:
-
diff --git a/setup.py b/setup.py
index a35595e..298ec4a 100644
--- a/setup.py
+++ b/setup.py
@@ -18,7 +18,6 @@ desc = 'Sphinx extension to show commit history in version control system'
 requires = [
     'GitPython',
     'Sphinx',
-    'six',
 ]
 
diff --git a/sphinxcontrib/__init__.py b/sphinxcontrib/__init__.py
index 1bfee45..69b0b13 100644
--- a/sphinxcontrib/__init__.py
+++ b/sphinxcontrib/__init__.py
@@ -1,4 +1,3 @@
-# -*- coding: utf-8 -*-
"""
sphinxcontrib
```

(continues on next page)

(continued from previous page)

```

~~~~~
diff --git a/sphinxcontrib/repository/__init__.py b/sphinxcontrib/repository/__init__.py
index 77ca293..0b16719 100644
--- a/sphinxcontrib/repository/__init__.py
+++ b/sphinxcontrib/repository/__init__.py
@@ -1,6 +1 @@
-# -*- coding: utf-8 -*-
-from __future__ import absolute_import
-
    from .git import GitRepository # noqa
    from .mercurial import MercurialRepository # noqa
    from .utils import find_repository_top # noqa
diff --git a/sphinxcontrib/repository/_git.py b/sphinxcontrib/repository/_git.py
index 8d26616..a4f560f 100644
--- a/sphinxcontrib/repository/_git.py
+++ b/sphinxcontrib/repository/_git.py
@@ -1,6 +1,3 @@
-# -*- coding: utf-8 -*-
-from __future__ import absolute_import
-
    import re
-
        import gitdb
diff --git a/sphinxcontrib/repository/_mercurial.py b/sphinxcontrib/repository/_mercurial.py
deleted file mode 100644
index 15da53b..0000000
--- a/sphinxcontrib/repository/_mercurial.py
+++ /dev/null
@@ -1,152 +0,0 @@
-# -*- coding: utf-8 -*-
-from __future__ import absolute_import
-
-import os
-import re
-
-try:
-    from mercurial import ui, hg, commands
-    from mercurial.error import RepoLookupError
-except ImportError:
-    pass
-
-from .utils import find_hosting_site, find_repository_top
-from .utils import log
-from .utils import make_commit_url
-
-
-class MercurialRepository(object):
-
    LOG_PATTERN = re.compile(r'(?P<type>\w+):[ \t\s]+(?P<value>.*)')
    URL_PATTERN = re.compile(
        r"""
            ssh://hg@bitbucket.org/(?P<account>.*?)/(?P<repository_name>.*?)\$
            |https://.+@?bitbucket.org/(?P<account>.*?)/(?P<repository_name>.*?)\$
            """", re.VERBOSE
    )

```

(continues on next page)

(continued from previous page)

```
- def __init__(self, limit, path):
-     self.limit = limit
-     self.ui = ui.ui()
-     self.raw = hg.repository(self.ui, path=path)
-     self._changeset = {}
-     self._commits = []
-     self.set_default_path(path)
-
-     def set_default_path(self, path):
-         # FIXME: how to get default path
-         # for some reason, commands.paths() doesn't return default path
-         self.default_path = ''
-         with open(os.path.join(path, '.hg', 'hgrc')) as f:
-             for line in f:
-                 if line.startswith('default'):
-                     self.default_path = line.split('=')[1].strip()
-                     break
-
-     def read_changeset_lines(self, lines):
-         is_found, commit = False, {}
-         for index, line in enumerate(lines, 1):
-             m = re.match(self.LOG_PATTERN, line)
-             if m is not None:
-                 log_info = m.groupdict()
-                 type_ = log_info.get('type', None)
-                 value = log_info.get('value', None)
-                 if type_ is not None:
-                     if type_ == 'changeset':
-                         if is_found:
-                             index -= 1
-                             break
-                         is_found = True
-                         revision, sha = value.split(':')
-                         commit['revision'] = int(revision)
-                         commit['sha'] = sha
-                         commit[type_] = value
-                     return index, commit
-
-     def get_commit(self, revision):
-         self.ui.pushbuffer()
-         try:
-             commands.log(self.ui, self.raw, rev=[str(revision)])
-         except RepoLookupError as err:
-             log.error(err)
-             log.warn("Not found '%s' in mercurial repository" % revision)
-         else:
-             lines = self.ui.popbuffer().decode('utf-8').split('\n')
-             index, commit = self.read_changeset_lines(lines)
-             changeset = commit.get('changeset')
-             if changeset is not None:
-                 self._commits.append(commit)
-                 self._changeset[changeset] = commit
-             return commit
-
-     def get_commits(self, revision=None, limit=None):
-         if revision is not None:
```

(continues on next page)

(continued from previous page)

```

-
-         self.get_commit(revision)
-         self.limit = 1
-         return self._commits[:self.limit]
-
-
-     if len(self._commits) == 0 or limit is not None:
-         self._commits[:] = []
-         if limit is not None:
-             self.limit = limit
-
-
-         self.ui.pushbuffer()
-         commands.log(self.ui, self.raw, limit=self.limit + 1)
-         lines = self.ui.popbuffer().decode('utf-8').split('\n')
-
-
-         while len(lines) != 0:
-             index, commit = self.read_changeset_lines(lines)
-             changeset = commit.get('changeset')
-             if changeset is not None:
-                 self._commits.append(commit)
-                 self._changeset[changeset] = commit
-             lines = lines[index:]
-
-
-         return self._commits[:self.limit]
-
-
-     def get_commit_url(self, revision):
-         site = find_hosting_site(self.default_path)
-         if site is None:
-             return ''
-
-
-         return make_commit_url(
-             self.URL_PATTERN, self.default_path, site, revision)
-
-
-     def get_diff(self, revision):
-         self.ui.pushbuffer()
-         revisions = [revision - 1, revision]
-         commands.diff(self.ui, self.raw, rev=revisions)
-         diff_text = self.ui.popbuffer()
-         try:
-             diff = diff_text.decode('utf-8')
-         except UnicodeDecodeError as err:
-             log.error(err)
-             msg = 'Supports utf-8 encoding only, '\
-                  'so ignore diff text from revisions: %s' % (revisions)
-             log.warn(msg)
-             diff = ''
-         return diff
-
-
-
-     def get_repo(number_of_revisions, path):
-         repository_path = find_repository_top(path, '.hg')
-         if repository_path is None:
-             return None
-         return MercurialRepository(number_of_revisions, repository_path)
-
-
-
-     def test():
-         r = get_repo(10, '.')
-
```

(continues on next page)

(continued from previous page)

```
-    commits = r.get_commits(max_count=3)
-    print(commits)
-
-    for commit in commits:
-        print(r.get_diff(commit['revision']))
-
-    commit_url = r.get_commit_url(commits[0]['sha'])
-    print(commit_url)
-
-
-if __name__ == '__main__':
-    test()
diff --git a/sphinxcontrib/repository/utils.py b/sphinxcontrib/repository/utils.py
index 95c205b..0a4dcdf 100644
--- a/sphinxcontrib/repository/utils.py
+++ b/sphinxcontrib/repository/utils.py
@@ -1,8 +1,4 @@
-# -*- coding: utf-8 -*-
-from __future__ import absolute_import
-
import logging
import os
import re

HOSTING_SERVICE = {
@@ -31,18 +27,6 @@ def find_hosting_site(url):
    return None

def find_repository_top(current_dir, conf_dir):
    repository_dir = os.path.abspath(os.path.join(current_dir, conf_dir))
    if repository_dir == os.path.abspath(os.sep):
        return None
-
    if os.path.exists(repository_dir) and os.path.isdir(repository_dir):
        return os.path.abspath(current_dir)
    else:
        parent_dir = os.path.join(current_dir, os.path.pardir)
        return find_repository_top(parent_dir, conf_dir)
-
-
def make_commit_url(pattern, path, site, revision):
    m = re.match(pattern, path)
    if m is None:
diff --git a/sphinxcontrib/vcs.py b/sphinxcontrib/vcs.py
index a95a0ba..dee234b 100644
--- a/sphinxcontrib/vcs.py
+++ b/sphinxcontrib/vcs.py
@@ -1,19 +1,18 @@
-# -*- coding: utf-8 -*-
import os
from datetime import datetime

-import six
from docutils import nodes
from docutils.parsers.rst import Directive
from docutils.parsers.rst import directives
```

(continues on next page)

(continued from previous page)

```
+from sphinx.util import logging
from sphinx.util.osutil import copyfile

from .repository import GitRepository
-from .repository import MercurialRepository
-from .repository import find_repository_top

__version__ = '0.1.0'

+logger = logging.getLogger(__name__)
+
CSS_CLASS = {
    'diff': ['contrib-vcs-diff', 'toggle-close'],
    'directive': ['contrib-vcs'],
@@ -43,7 +42,7 @@ class BaseDirective(Directive):
}

def _make_message_node(self, message, sha):
-    message, classes = six.text_type(message), []
+    message, classes = message, []
    if OPTION_INCLUDE_DIFF in self.options:
        classes = CSS_CLASS['message']
    return nodes.strong(ids=[sha], text=message, classes=classes)
@@ -79,12 +78,12 @@ class GitDirective(BaseDirective):
    item = nodes.list_item()

    item.append(self._make_message_node(commit.message, commit.hexsha))
-    item.append(nodes.inline(text=six.text_type(' by ')))
-    item.append(nodes.emphasis(text=six.text_type(commit.author.name)))
-    item.append(nodes.inline(text=six.text_type(' at ')))
+    item.append(nodes.inline(text=' by '))
+    item.append(nodes.emphasis(text=commit.author.name))
+    item.append(nodes.inline(text=' at '))

    commit_date = datetime.fromtimestamp(commit.authored_date)
-    item.append(nodes.emphasis(text=six.text_type(commit_date)))
+    item.append(nodes.emphasis(text=commit_date))

    if OPTION_WITH_REF_URL in self.options:
        ref_url = repo.get_commit_url(commit.hexsha)
@@ -98,36 +97,6 @@ class GitDirective(BaseDirective):
    return item

-class MercurialDirective(BaseDirective):
-
-    def get_repo(self, number_of_revisions):
-        env = self.state.document.settings.env
-        src_dir = find_repository_top(env.srccdir, '.hg')
-        if src_dir is None:
-            return None
-        return MercurialRepository(number_of_revisions, src_dir)
-
-    def get_changelog(self, repo, commit):
-        item = nodes.list_item()
-
-        item.append(self._make_message_node(commit['summary'], commit['sha']))
```

(continues on next page)

(continued from previous page)

```
-         item.append(nodes.inline(text=six.text_type(' by ')))
-         item.append(nodes.emphasis(text=six.text_type(commit['user'])))
-         item.append(nodes.inline(text=six.text_type(' at ')))
-         item.append(nodes.emphasis(text=six.text_type(commit['date'])))

-
-         if OPTION_WITH_REF_URL in self.options:
-             ref_url = repo.get_commit_url(commit['sha'])
-             ref = nodes.reference('', commit['sha'], refuri=ref_url)
-             item.append(nodes.paragraph('', '', ref))

-
-         if OPTION_INCLUDE_DIFF in self.options:
-             diff = repo.get_diff(commit['revision'])
-             item.append(self._make_diff_node(diff, commit['sha']))

-
-         return item

-
- CSS_FILES = ['contrib-vcs.css']
JS_FILES = ['contrib-vcs.js']

@@ -149,17 +118,16 @@ def copy_assets(app, exception):
    current_path = os.path.abspath(os.path.dirname(__file__))
    static_path = app.builder.config.html_static_path[0]

-    app.info('Copying vcs stylesheet/javascript...', nonl=True)
+    logger.info('Copying vcs stylesheet/javascript...', nonl=True)
    for file_ in CSS_FILES + JS_FILES:
        dest = os.path.join(app.builder.outdir, static_path, file_)
        source = os.path.join(current_path, static_path, file_)
        copyfile(source, dest)
-    app.info('done')
+    logger.info('done')

def setup(app):
    app.add_directive('git', GitDirective)
-    app.add_directive('mercurial', MercurialDirective)

    # copying css/js to _static
    app.connect('builder-initied', add_assets)
```

- drop python 2.7 support (mercurial) by Tetsuya Morimoto at 2018-11-17 11:20:50
e5f1e488e5a284ec4a1106adba8d7353b3c233f1

```
diff --git a/README.md b/README.md
index ce973b7..2738134 100644
--- a/README.md
+++ b/README.md
@@ -24,21 +24,8 @@ Then, repository directives are available as follows.
:with_ref_url:
:include_diff:

-
-### Mercurial
-
-.. mercurial::
```

(continues on next page)

(continued from previous page)

```

-
-      :number_of_revisions: 20
-      :with_ref_url:
-      :include_diff:
-
For more information have a look at [the documentation] (https://pythonhosted.org/  
sphinxcontrib-vcs/).

-## Note
-
-[Mercurial] (https://www.mercurial-scm.org/) supports Python 2.x only.
-So *sphinxcontrib-vcs* supports the *mercurial* directive on Python 2.7.
-
## Acknowledgments

*sphinxcontrib-vcs* is inspired from the [sphinx-git] (https://github.com/  
OddBloke/sphinx-git).
diff --git a/setup.py b/setup.py
index c14fe38..a35595e 100644
--- a/setup.py
+++ b/setup.py
@@ -1,8 +1,5 @@
-# -*- coding: utf-8 -*-
import re
import sys
-
from setuptools import find_packages, setup
+from setuptools import setup

try:
@@ -24,9 +21,6 @@
    'six',
]

-if sys.version_info < (3, 0):
-    requires.append('Mercurial')
-

setup(
    name='sphinxcontrib-vcs',
@@ -38,12 +32,11 @@
        'Development Status :: 4 - Beta',
        'Intended Audience :: Developers',
        'Operating System :: OS Independent',
-
        'Programming Language :: Python :: 2',
-
        'Programming Language :: Python :: 2.7',
        'Programming Language :: Python :: 3',
-
        'Programming Language :: Python :: 3.3',
        'Programming Language :: Python :: 3.4',
        'Programming Language :: Python :: 3.5',
+
        'Programming Language :: Python :: 3.6',
+
        'Programming Language :: Python :: 3.7',
        'Programming Language :: Python :: Implementation :: CPython',
        'Topic :: Software Development :: Libraries',
        'Environment :: Console',
@@ -55,10 +48,10 @@
        url='https://github.com/t2y/sphinxcontrib-vcs',

```

(continues on next page)

(continued from previous page)

```
license='BSD',
author='Tetsuya Morimoto',
- author_email='tetsuya dot morimoto at gmail dot com',
+ author_email='tetsuya.morimoto@gmail.com',
zip_safe=False,
platforms='any',
- packages=find_packages(),
+ packages=['sphinxcontrib'],
namespace_packages=['sphinxcontrib'],
include_package_data=True,
install_requires=requires,
diff --git a/tox.ini b/tox.ini
index 952ad09..7ed87a0 100644
--- a/tox.ini
+++ b/tox.ini
@@ -1,5 +1,5 @@
 [tox]
-envlist = py27, py33, py34, py35
+envlist = py34, py35, py36, py37

[testenv]
passenv =
```

- **fix minor typos** by *Tetsuya Morimoto* at 2016-09-07 09:30:59 2c8a68d86b3fd4a94c26d83a828873aa3c8037a3

```
diff --git a/docs/_options.rst b/docs/_options.rst
index 5d0ff0c..4889ba3 100644
--- a/docs/_options.rst
+++ b/docs/_options.rst
@@ -1,7 +1,7 @@
Options
------

-Each repository directive take these options.
+The repository directive takes these options.

- **number_of_revisions**: positive integer

diff --git a/docs/git.rst b/docs/git.rst
index 5392cde..4ece3a3 100644
--- a/docs/git.rst
+++ b/docs/git.rst
@@ -29,7 +29,7 @@ Particular commit log
::

.. git::

- :revision: 69ef5f984f8564dceea0e90e8d169b1807247d8a
+ :revision: 33e6b629ed3d6ed63f64136661642f594b1f4d6f
:with_ref_url:
:include_diff:
```

- **update to use upload_sphinx command for documentation** by *Tetsuya Morimoto* at 2016-09-06 05:17:56 c56f2bd20a2266320dfcb50a89a120713c6b940c

```
diff --git a/setup.cfg b/setup.cfg
```

(continues on next page)

(continued from previous page)

```
index 917b7a4..31e9f22 100644
--- a/setup.cfg
+++ b/setup.cfg
@@ -13,3 +13,6 @@ release = check -r -s register sdist bdist_wheel upload
[check]
strict = 1
restructuredtext = 1
+
+[upload_sphinx]
+upload-dir = docs/_build/html
```

- **update documentation link in README** by *Tetsuya Morimoto* at 2016-09-06 05:17:11
d26ac0cac5c00688c334fdbf5c1dd488ae6ce0a7

```
diff --git a/README.md b/README.md
index 0c7ca58..ce973b7 100644
--- a/README.md
+++ b/README.md
@@ -32,7 +32,7 @@ Then, repository directives are available as follows.
      :with_ref_url:
      :include_diff:

-For more information have a look at the documentation.
+For more information have a look at [the documentation] (https://pythonhosted.org/  
→sphinxcontrib-vcs/).
```

1.3 Particular commit log

```
.. git::  
    :revision: 33e6b629ed3d6ed63f64136661642f594b1f4d6f  
    :with_ref_url:  
    :include_diff:
```

- **initial commit** by *Tetsuya Morimoto* at 2016-09-02 14:14:28 33e6b629ed3d6ed6f64136661642f594b1f4d6f

```
diff --git a/README.md b/README.md
new file mode 100644
index 0000000..b6f2af0
--- /dev/null
+++ b/README.md
@@ -0,0 +1 @@
+# Sphinxcontrib-vcs
```

**CHAPTER
TWO**

ACKNOWLEDGMENTS

sphinxcontrib-vcs is inspired from the [sphinx-git](#).

CHAPTER
THREE

INDICES AND TABLES

- genindex
- modindex
- search